

KRONOS 2233

Titanium Dioxide

for polycarbonate

Applications

- Polycarbonate
- Polycarbonate blends
- Engineering plastics

Properties

KRONOS 2233 Titanium Dioxide

- Prevents the polycarbonate degradation seen using conventional TiO₂
- Is readily wetted and dispersed
- Delivers very high tinting strength and a bluish tone
- Produces pure, brilliant tints
- Ensures excellent coloring properties at high processing temperatures

Product Characteristics

Production	rutile pigment produced by the chloride process
Surface treatment	aluminum and polysiloxane compounds
TiO ₂ content (DIN EN ISO 591)*	≥ 95.4%
Standard classification (DIN EN ISO 591-1)	R 2
ASTM D 476	Type II
Density (DIN EN ISO 787-10)*	4.2 g/cm ³
Bulking value*	0.24 l/kg (0.03 gal/lb)
Oil absorption (DIN EN ISO 787-5)*	14 g/100 g pigment
Color index	Pigment White 6 (77891)
CAS No.	13463-67-7
REACH Registration No.	01-2119489379-17-xxxx

* Typical value

This information pertains solely to the identified product and includes our reliance on testing and information from third parties as of the date hereof. It is not intended to serve as legal, regulatory, or safety advice. It remains the sole responsibility of the customer to determine the suitability of the product when used in specific processes and applications or combined with other materials and to ensure compliance with all relevant laws, regulations, and standards governing those uses. The provision of this information DOES NOT CONSTITUTE A WARRANTY, GUARANTEE, OR REPRESENTATION OF ANY KIND REGARDING PERFORMANCE, SUITABILITY, STABILITY OR OTHERWISE, including compliance with any law, regulation, or industry standard. No contractual obligations or rights, either express or implied, are created between KRONOS and any recipient of this information. © Kronos Worldwide, Inc., KRONOS™ and logo designs associated therewith are copyrights and trademarks of Kronos Worldwide, Inc. and/or its subsidiaries or affiliates.